




HF-3040

UV HYBRID PRINTER



Self-development



long life




High precision




low cost

TECHNICAL PARAMETER

Model	HF-3040
Printhead	Epson13200-U1 HD Printhead
Printhead Quantity	1
Print Speed	0.28m²/h~3m²/h
Print Width	Platform: 297*420mm ; Roll to roll device: supporting roll width 30-290mm,diameter 150mm, Inner core diameter:76mm ; Rotary device: supporting cylinder length 20-230mm,diameter 30-90mm
Print Media	Thickness1mm~90mm
Ink Type	Environmental friendly UV curing ink
Color Configuration	Standard: CMYK+W+V Optional: YMCK LC LM+W
RIP Software	RIIN/Flexiprint/Maintop/NeoStampa
Print Media	Glass, plates, various signs, crystal, PVC, acrylic, leather plastic, etc.
Photo Format	TIFF,JPEG,PDF,EPS,PNG,AI, BMP,etc.
Computer Configuration	Processor: Intel Core i5-13500H or above. Memory: 16GB memory. Graphics card: independent graphics card; Storage: 1TB SSD Network card:RG45 Gigabit network card with Intel chip+"Jumbo Packet-9014" mode(for CCD camera connection)
Rated Voltage/Power	220V 50HZ~60HZ 500W
Work Environment	Temperature:18°C~28°C Humidity:40%~60%
Machine Size/Weight	1020*830*615mm 114kg
Packaging Size/Weight	1160*1030*760mm 124kg




UV lamp



Rotary clamp



CCD visual positioning system(Optional)



Cylinder printing mode