


HR1602 UV

huenü®
IMPULSAMOS OPORTUNIDADES



Piezoelectric nozzle
压电喷头



1200x720
dpi
高精度



3.8pl
墨滴大小



V.S.O.S



Laser Cable
光纤



1000LPH
每分钟长



Automatic cleaning
自动清洗



Stable printing
稳定

Printing Speed

DPI	PASS	Type	1H	2H	4H
720*1200	4PASS	Weak Feather 弱羽化	19.75m ² /H	37.09m ² /H	63.4m ² /H
		Normal Feather 中羽化	16.11m ² /H	28.69m ² /H	54.6m ² /H
		Strong Feather 强羽化	12.72m ² /H	20.58m ² /H	36.74m ² /H
720*1800	6PASS	Weak Feather 弱羽化	12.97m ² /H	24.72m ² /H	40.11m ² /H
		Normal Feather 中羽化	10.65m ² /H	19.18m ² /H	33.6m ² /H
		Strong Feather 强羽化	8.28m ² /H	13.79m ² /H	27.3m ² /H
720*2400	8PASS	Weak Feather 弱羽化	9.98m ² /H	18.54m ² /H	32.49m ² /H
		Normal Feather 中羽化	8.11m ² /H	13.84m ² /H	25.36m ² /H
		Strong Feather 强羽化	6.49m ² /H	10.26m ² /H	17.39m ² /H

Photo 细节展示



Boards& RIP 板卡和软件	Boards(板卡) Password(密码) Rip Software(RIP软件)	Hoson Boards(汉森) Build in Boards & Showing in Software(板卡自带) PhotoPRINT Rip Software(美国PP软件)
Body 机架	Main Girder Structure(主梁支撑) Y-Axis(Y轴) Beam(运动横梁) Linear Guide Way(导轨) Pinch Roller(压轮组件) Printing Bed(打印平台) Suction System(平台吸风) LED lighting(平台LED)	160*60*3mm Square Tube(160*60*3方管) 20mm Diameter(20毫米主轴) Aluminium Beam(铝合金横梁) THK linear guide way With two Block(THK静音导轨) Hi Precision 3 level Pinch roller(高精度三段式压轮组件) 144mm Wide Printing Bed(144毫米宽打印平台) Adjustable Vacuum Suction System(可调节吸风) Printing Bed Lighting System(平台LED照明)
Carriage 小车	Belt(皮带) Chain(拖链) Cable(主数据线) Power Cable(电源线) Encoder(光栅解码器) Carriage Lifting(升降) Capping(保湿) Anti Collision(防撞)	Italy MEGADYNE Belt(意大利麦高迪皮带) Germany Igus Drag Chain(德国IGUS静音拖链) Fiber(光纤) Germany Igus Power Cable(德国IGUS高柔电缆) 180DPI(9730) Manual type Carriage Lifting System(手动升降小车) Automatic Capping & Wiping system(全自动吸墨和刮墨墨栈) Anti Collision System(小车防撞系统)
Motor 电机	X Motor(X轴电机) Y Motor(Y轴电机) XY Motor Bracket(电机支架)	Leadshine 180W DC Servo Motor(雷赛180瓦直流电机) Leadshine 180W DC Servo Motor(雷赛180瓦直流电机) Metal Brackets(金属支架)
F&T 收放料	Paper Sensor(缺纸感应探头) Feeding and Take up(收放料) Leveling Stand(防抖地撑)	Paper Out Warning Sensor(缺纸感应探头) Double Industry motor(工业型双动力收放料系统) Leveling Stand(防抖地撑)
Ink Supply 供墨	INK Supply System(供墨) Main INK tank(主墨桶) Damper(墨囊) Ink Pump(墨泵)	Bulk ink Supply system(大供墨系统) 1.5L Main INK tank(1.5L容量主墨桶) Negative type Damper(负压墨囊) SPD Ink Pump(赛普达墨泵)
Heating &Drying 加热和烘干	Drying System(干燥) Heating Control Panel(加热控制面板) Heating System(加热) Carriage Plate Heater(小车底板加热)	LED Curing System(LED固化系统) 3 in 1 Heating Control Panel(多合一控制系统) Rear-Printing Bed-Front 3 Heaters(前中后三加热) 24V DC Heater(直流24V加热片)
Packing 包装	Printer Name Plate(铭牌) Printer Size(打印机尺寸)L*W*H Printer Packing (打印机包装) N.W.(净重)/G.W.(毛重) Packingsize(包装尺寸) 20GP/40HQ	Alumimuml Name Plate (铝制CE铭牌) 2585*670*1300 Wooden Box(免熏蒸木制包装箱) 180KG/240KG 2700*570*650 24PCS/64PCS

Container Capacity 装柜说明

