

huenü®

IMPULSAMOS OPORTUNIDADES
DTF Printing Machine

HR 3002 DT



Technical Parameters Of DTF Printing Machine

型号/Item Model	HR 3002 DT
喷头/print head	EPSON - i1600 / i3200
打印精度/速度/Print Accuracy/speed	4pass: 8m ² /h
	6pass: 5m ² /h
	8pass: 3m ² /h
墨水/Ink	白墨 烫画 DTF
最大宽幅/Maximum Width	330mm
打印介质/Print Medium	PET 烫画膜 PET Film
打印接口/Printer Interface	RJ45 网线接口 Cable interface
RIP 软件/RIP Software	Maintop 6.1, Photoprint Print Factory
功率/Power	400W
电源要求/Power Requirement	AC110V +/- 10% AC220V +/- 10% 50/60Hz
操作环境/Operating Environments	温度/Temperature: 20°C - 35°C 湿度/Humidity: 35%RH ~ 65%RH
机身尺寸(长×宽×高)/Dimensions of Printer(L x W x H)	820 x 503 x 472 mm
外包装尺寸(长×宽×高)/Dimensions of Packing(L x W x H)	970 x 760 x 620mm
净重/Net Weight	65KG
毛重/Weight	88KG

Shaker Parameter



型号/Item Model	D300-抖粉机 D300 Shaker
最大宽幅/Maximum Width	330mm
操作环境/Operating Environments	温度/Temperature: 20°C - 35°C, 湿度/Humidity: 35%RH - 65%RH
功率/Power	3600W
机身尺寸(长×宽×高) Dimensions of Printer(L x W x H)	1250 x 720 x 970 mm
外包装尺寸(长×宽×高) Dimensions of Packing (L x W x H)	1350 x 800 x 1040mm
净重/Net Weight	110KG
毛重/Weight	140KG