

huenü®

IMPULSAMOS OPORTUNIDADES

DTF Printing Machine

HR 6002 DT



Technical Parameters Of DTF Printing Machine

型号 Item Model	HR 6002 DT
喷头/print head	EPSON-i1600 / i3200
打印精度/速度/Print Accuracy/speed	4pass: 8m ² /h
	6pass: 5m ² /h
	8pass: 3m ² /h
墨水/Ink	白墨烫画DTF
最大宽幅/Maximum Width	620mm
打印介质/Print	PET烫画膜PET Film
打印接口/Printer	RJ45 网线接口/Cable interface
RIP软件/RIP Software	Maintop 6.1 Photoprint Print Factory
功率/Power	400W
电源要求/Power Requirement	AC110V +/- 10% AC220V +/- 10% 50/60Hz
操作环境/Operating Environments	温度/Temperature: 20°C - 35°C, 湿度/Humidity: 35%RH ~ 65%RH
机身尺寸(长×宽×高)/Dimensions of Printer (LxWxH)	1150 x 610 x 500 mm
外包装尺寸(长×宽×高)/Dimensions of Packing (LxWxH)	1300*750-560mm
净重/Net Weight	88KG
毛重/Weight	113KG

Shaker Parameter



型号/Item Model	D300-抖粉机 D300 Shaker
最大宽幅/Maximum Width	330mm
操作环境/Operating Environments	温度/Temperature: 20°C - 35°C, 湿度/Humidity: 35%RH ~ 65%RH
功率/Power	3600W
机身尺寸(长×宽×高)/Dimensions of Printer (LxWxH)	1250 × 720 × 970 mm
外包装尺寸(长×宽×高)/Dimensions of Packing (LxWxH)	1350*800*1040mm
净重/Net Weight	110KG
毛重/Weight	140KG