

HR 1602 ES



Piezoelectric nozzle
压电喷头



High Resolution
高精度



Drop
墨滴大小



VSDS



Low Cable
低缆



Long life
寿命长



Automatic Cleaning
自动清洗



Stable Printing
高稳定

Printing Speed

DPI	PASS	Type	1H	2H
720*1200	4PASS	Weak Feather 弱羽化	19.75m ² /H	37.09m ² /H
		Normal Feather 中羽化	16.11m ² /H	28.69m ² /H
		Strong Feather 强羽化	12.72m ² /H	20.58m ² /H
720*1800	6PASS	Weak Feather 弱羽化	12.97m ² /H	24.72m ² /H
		Normal Feather 中羽化	10.65m ² /H	19.18m ² /H
		Strong Feather 强羽化	8.28m ² /H	13.79m ² /H
720*2400	8PASS	Weak Feather 弱羽化	9.98m ² /H	18.54m ² /H
		Normal Feather 中羽化	8.11m ² /H	13.84m ² /H
		Strong Feather 强羽化	6.49m ² /H	10.26m ² /H

Photo 细节展示



Boards& RIP 板卡和软件	Boards(板卡) Password(密码)	● Hoson Boards(汉森) Build in Boards & Showing in Software(板卡自带)
Body 机架	Main Girder Structure(主梁支撑)	160*60*3mm Square Tube(160*60*3方管)
	Y-Axis(Y轴)	20mm Diameter(20毫米主轴)
	Beam(运动横梁)	Aluminium Beam(铝合金横梁)
	Linear Guide Way(导轨)	THK linear guide way With two Block(THK静音导轨)
	Pinch Roller(压轮组件)	Hi Precision 3 level Pinch roller(高精度三段式压轮组件)
	Printing Bed(打印平台)	144mm Wide Printing Bed(144毫米宽打印平台)
	Suction System(平台吸风)	Adjustable Vacuum Suction System(可调节吸风)
Carriage 小车	LED lighting(平台LED)	Printing Bed Lighting System(平台LED照明)
	Belt(皮带)	Italy MEGADYNE Belt(意大利麦高迪皮带)
	Chain(拖链)	Germany Igus Drag Chain(德国IGUS静音拖链)
	Cable(主数据线)	Fiber(光纤)
	Power Cable(电源线)	Germany Igus Power Cable(德国IGUS高柔电缆)
	Encoder(光栅解码器)	180DPI(9730)
	Carraige Lifting(升降)	Manual type Carraige Lifting System(手动升降小车)
Motor 电机	Capping(保湿)	Automatic Capping & Wipping system(全自动吸墨和刮墨系统)
	Anti Collision(防撞)	Anti Collision System(小车防撞系统)
	X Motor(X轴电机)	● Leadshine 180W/ DC Servo Motor(雷赛180瓦直流电机)
F&T 收放料	Y Motor(Y轴电机)	Leadshine 180W/ DC Servo Motor(雷赛180瓦直流电机)
	XY Motor Bracket(电机支架)	Metal Brackets(金属支架)
Ink Supply 供墨	Feeding and Take up(收放料)	Double Industry motor(工业型双动力收放料系统)
	Leveling Stand(防抖地撑)	Leveling Stand(防抖地撑)
	INK Supply System(供墨)	Bulkink Supply system(大供墨系统)
Heating &Drying 加热和烘干	Main INK tank(主墨桶)	1.5L Main INK tank(1.5L容量主墨桶)
	Damper(墨囊)	Negative type Damper(负压墨囊)
	Ink Pump(墨泵)	SPD Ink Pump(赛普达墨泵)
	Drying System(干燥)	LED Curing System(LED固化系统)
Packing 包装	Heating Control Panel(加热控制面板)	3 in 1 Heating Control Panel(多合一控制系统)
	Heating System(加热)	Rear-Printing Bed-Front 3 Heaters(前中后三加热)
	Carriage Plate Heater(小车底板加热)	24V DC Heater(直流24V加热片)
	Printer Name Plate(铭牌)	Aluminuml Name Plate (铝制CE铭牌)
	Printer Size(打印机尺寸)L*W*H	2785*670*1300
	Printer Packing (打印机包装)	V/ooden Box(免熏蒸木制包装箱)
	N.W.(净重)/G.W.(毛重)	180KG;200KG/240KG;270KG
	Packingsize(包装尺寸)	2900*570*650
	20GP/40HQ	24PCS/64PCS

